



Shenzhen Westart Technology Co.,Ltd.

Add.: 3rd Longcheng industrial Area, Long Gang District,Shenzhen,China,518000

Email: sales@szwestart.com

Web.: www.szwestart.com

## Photo



## Advantage

- Low temperature discharge
- Fast charge
- High energy density
- Reasonable design
- maximum use of limited space
- Longer service life
- Less weight
- High rigidity

## Specification

Nominal Capacity		153Ah@0.33C Discharging
Operating voltage(V)	55°C≤T<0°C	11.2~17.2
	-20°C<T≤0°C	10~17.2
	T≤-20°C	8.4~17.2
Module total energy(0.33C,2.8V~4.3V,25°C)		≥2264.4Wh
Configuration		1P4S
Coulombic efficiency (@25°C, 1C charge to 4.3V,0.05C charge to single cell 4.3V, standing by to target temperature, then 1C discharge)	-30°C	80%
	-20°C	85%
	-10°C	87%
	0°C	92%
	10°C	94%
	25°C	100%
	50°C	103%
Module self discharge rate( 60%SOC shipment)		<3%(1st month) <2%(2nd month)
SOC operating range		5%~97%
Module	Charging Current	1C continuous
	Discharging Current	1.5C continuous /4C peak(10 seconds)
Operation Temperature	Charging	-20°C~55°C
	Discharging	-30°C~55°C
Weight(Kg)		11.2±0.3
Size(mm)		355*151*108.5
Module energy density		206Wh/Kg
Module cycle life		≥2000(0.5C/1C,100%DOD,25°C)

## Application

Ideal for Electric Vehicles.